

### Part number list

BC0702A□□□□\$

### Feature

1. Built-in controller RW1068
2. 12x12 dots character
3. Japanese/Chinese/Korean Font
4. +5V single power supply
5. (Option) LED backlight
6. (Option) +3V power supply
7. (Option) negative voltage for +3V power

### Pin Assignment

Pin No.	Symbol	Description
1	V <sub>SS</sub>	GND
2	V <sub>DD</sub>	+5V (+3V option)
3	V <sub>O</sub>	Contrast Adjustment
4	RSP	H/L register select signal
5	RWP	H/L read/white signal
6	EP	H --> L enable signal
7	DB0	H/L data bus line
8	DB1	H/L data bus line
9	DB2	H/L data bus line
10	DB3	H/L data bus line
11	DB4	H/L data bus line
12	DB5	H/L data bus line
13	DB6	H/L data bus line
14	DB7	H/L data bus line

### Mechanical Data

Item	Standard Value	Unit
Module Dimension	85.0 x 30.0	mm
Viewing Area	66.0 x 16.0	mm
Dot Size	0.50 x 0.50	mm
Character Size	6.44 x 6.44	mm

### Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Input Voltage	VDD	5	V
Recommended LCD Driving Voltage for Normal Temp. Version module @ 25°C	VDD-VO	4.0	V

### Mechanical Drawing

