

### Part number list

SC1001A□□□-□□-□□-□

### Feature

1. Built-in controller ST7066 or equivalent
2. +5V single power supply
3. (Option) +3V power supply

### Pin Assignment

Pin No.	Symbol	Description
1	V <sub>SS</sub>	Supply Ground
2	V <sub>DD</sub>	Supply Voltage
3	V <sub>O</sub>	Contrast Adjustment
4	RS	Register Select
5	R/W	Read/Write
6	E	Enable signal
7	DB0	Data bus line
8	DB1	Data bus line
9	DB2	Data bus line
10	DB3	Data bus line
11	DB4	Data bus line
12	DB5	Data bus line
13	DB6	Data bus line
14	DB7	Data bus line
15	A	Power supply for B/L +
16	K	Power supply for B/L -

### Mechanical Data

Item	Standard Value	Unit
Module Dimension	80.0 x 36.0	mm
Viewing Area	65.0 x 16.0	mm
Dot Size	0.92 x 11.0	mm
Character Size	4.84 x 9.22	mm

### Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Input Voltage	V <sub>DD</sub>	5	V
Recommended LCD Driving Voltage for Normal Temp. Version module @ 25°C	V <sub>DD</sub> -V <sub>O</sub>	4.5	V

### Mechanical Drawing

