

### Part number list

SC1602P□□□-□□-□□-□

### Feature

1. Built-in controller ST7066 or equivalent
2. +5V single power supply
3. (Option) +3V power supply

### Pin Assignment

Pin No.	Symbol	Description
1	V <sub>SS</sub>	Supply Ground
2	V <sub>DD</sub>	Supply Voltage
3	V <sub>O</sub>	Contrast Adjustment
4	RS	Register Select
5	R/W	Read/Write
6	E	Enable signal
7	DB0	Data bus line
8	DB1	Data bus line
9	DB2	Data bus line
10	DB3	Data bus line
11	DB4	Data bus line
12	DB5	Data bus line
13	DB6	Data bus line
14	DB7	Data bus line
15	A	LED Power
16	K	LED Power

### Mechanical Data

Item	Standard Value	Unit
Module Dimension	53.0 x 20.0	mm
Viewing Area	36.0 x 10.0	mm
Dot Size	0.33 x 0.35	mm
Character Size	1.85 x 3.15	mm

### Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Input Voltage	V <sub>DD</sub>	5	V
Recommended LCD Driving Voltage for Normal Temp. Version module @ 25°C	V <sub>DD-VO</sub>	4.5	V

### Mechanical Drawing

