

Part number list

SG12832C□□□-□□-□□-□

Feature

1. Bult-in controller RW1065 or equivalent
2. Bult-in oscillation
3. +5V single power supply
4. 6800 interface

Pin Assignment

Pin No.	Symbol	Description
1	V _{SS}	Ground
2	V _{DD}	Power supply for logic
3	V _O	Contrast Adjustment
4	A0	Data/ Instruction select signal
5	CS1	Chip Select Signal for IC1
6	CS2	Chip Select Signal for IC2
7	NC	No connection
8	E	Enable Signal
9	R/W	Read/Write select signal
10~17	DB0~7	Data Bus Line
18	/RES	Reset Signal
19	A	Power supply for B/L +
20	K	Power supply for B/L -

Mechanical Data

Item	Standard Value	Unit
Module Dimension	84.0 x 44.0	mm
Active Area	58.84 x 14.68	mm
Dot Pitch	0.46 x 0.46	mm
Dot Size	0.42 x 0.42	mm

Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Input Voltage	V _{DD}	5.0	V
Recommended LCD Driving Voltage for Normal Temp. Version module @25°C	V _{DD-VO}	4.8	V

Mechanical Drawing

