



The EL320.256-F is a TFEL display for use in extreme operating conditions.

Lumineq® Thin Film Electroluminescence (TFEL) displays have the widest operating temperature range of commercially available technology.

TFEL displays are ideal for use in industrial, medical, transportation, military, public safety and other demanding applications.

Lumineq Thin Film Electroluminescent Display

Product highlights:

- Broad input voltage range: 11...30 VDC

General TFEL features and benefits:

- Instant ON in cold and hot temperatures
- No need for heating and cooling
- Very long lifetime
- Extremely stable brightness – measured 100,000 hours with > 85% left of initial luminance
- TFEL display brightness, contrast, viewing angle and response time are the same across the entire operating temperature range
- Wide viewing angle > 179° with crisp and clear image
- Very fast response time, < 1 ms
- Extremely rugged and solid TFEL display structure
- Very long production life time

Technical specifications:

Technology	Thin Film Electroluminescence
Color	TFEL-yellow
Viewing angle	179°, any viewing directions
Response time	< 1 ms
Luminance	77 cd/m ² typical areal (-F6) 25 cd/m ² typical areal (-FD6)
Resolution	320 × 256 pixels
Pixel pitch	0.30 × 0.30 mm
Weight	260 g (-F6 and -FD6) 310 g (FD8 V2)
Display size	130 × 110 × 31.1 mm (-F6 and -FD6)
Active area	95.9 × 76.7 mm
Supply voltages	5 and 11...30 VDC
Power	6.0 W, typical (-F6 and -FD6)
MTBF	> 50,000 hours (-F6 and -FD6)
Temperature	-F6 and -FD6: Operating: -25 to +65 °C Survival: -40 to +70 °C Storage: -40 to +85 °C
Humidity	93% RH, oper., IEC 68-2-3
Altitude	15,000 m, oper., above sea level
Shock	100 g-force, 4 ms, IEC 68-2-27
Vibration	20 to 500 Hz, 0.05 g ² /Hz random IEC 68-2-36, test Fdb
Interface	EL standard, 1 bit/clock
Interface	EL standard, 1 bit/clock

Ordering Information:

Product	Part number	Features
EL320.256-F6	996-5076-00LF	Non-ICEBrite™
EL320.256-FD6	996-5087-00LF	ICEBrite™

Beneq and Lumineq are registered trademarks of Beneq Oy. ICEBrite is a trademark of Beneq Oy. Technical information in this document is subject to change without notice. Sep/2014